

# STANLEY®

## SAFETY FOOTWEAR



# SAFETY FOOTWEAR

## PRODUCT GUIDE



It is important that you choose the right shoes with the right level of protection needed for your job. Here is a guide to the standards and levels of protection offered under the different categories of safety footwear.

The footwear protects the wearer's toes against risk of injury from falling objects and crushing when worn in industrial and commercial environments where potential hazards occur with the following protection plus, where applicable, additional protection.

Impact protection provided is 200 Joules.

Compression protection provided is 15,000 Newtons.

Additional protection may be provided, and is identified on the product by its marking as shown:

Categories of safety footwear:

Category	Type (*I) and (**II)	Additional Requirement
SB	I II	Safety basic requirements
S1	I	Closed seat region Antistatic properties Energy absorption at the seat region
S2	I	As S1 plus Water penetration and absorption of the upper Construction
S3	I	As S2 plus Penetration resistance Cleated outsole
S4	II	Antistatic properties Energy absorption at the seat region
S5	II	As S4 plus Penetration resistance Cleated outsole

\* Type I footwear is made from leather and other materials excluding all-rubber or all-polymeric footwear

\*\* Type II All -rubber (i.e. entirely vulcanized) or all-polymeric (i.e. entirely moulded) footwear

Description	Marking Code
Penetration resistance (1100 Newtons)	P
Electrical properties: Conductive (maximum resistance 100 kΩ) Antistatic (resistance range of 100 kΩ to 1000 MΩ) Electrically insulating footwear	C A I
Resistance to inimical environments: Insulation against heat Insulation against cold	HI CI
Energy absorption of seat region (20 Joules)	E
Water resistance	WR
Metatarsal protection	M
Ankle protection	AN
Upper: Water penetration and water absorption Cut resistant upper	WRU CR
Outsole: Resistance to hot contact	HRO
Marking of product for slip resistance properties	Marking Code
Ceramic tile with sodium lauryl sulphate	SRA
Steel with glycerol	SRB

\*Note: Slippage may still occur in certain environments.

## ICONS



resistant to 200 joules



chemical resistant



oil resistant



penetration resistant



water resistant



heat resistant to 300 °C



double density seat region



antistatic



non metallic

**GLOBE**

EN20345:2011-S1P



Black Black



Black Navy

**Features**

- Ripstop mesh upper
- Dual density outsole
- Puncture resistant midsole
- Removable dual density PU comfort insole

**Benefits**

- Sports styling
- Light weight and flexible
- Underfoot protection
- Ergonomic design

Upper	Ripstop Mesh Upper
Lining	Aerospacer
Insole	Removable Comfort Footbed
Outsole	Dual Density Rubber
Sizes	UK 6-12 EU 40-46



**TRADESMAN**

EN20345:2011-SB-P



Honey



Brown



Black

**Features**

- Buffalo nubuck upper
- Rubber/phylon outsole
- Puncture resistant midsole
- Removable dual density PU comfort insole

**Benefits**

- Top quality premium hide, long lasting
- Light weight and flexible
- Underfoot protection
- PU collar for comfort

Upper	Honey Buffalo Nubuck
Lining	Aerospacer
Insole	Removable Comfort Footbed
Outsole	Rubber/ Phylon Cemented
Sizes	UK 6-12 EU 40-46



**PULSE**

EN20345:2011-S1P



Black Black



Black Blue

Leather & mesh upper  
Dual density outsole  
Puncture resistant midsole  
Removable dual density PU comfort insole

**Benefits**

- Sports styling
- Light weight and flexible
- Underfoot protection
- Ergonomic design

Upper	Leather & Mesh
Lining	Aerospacer
Insole	Removable Comfort Footbed
Outsole	Dual Density Rubber
Sizes	UK 6-12 EU 40-46



**MELROSE**

EN20345:2011-S1P



Tan



Grey

**Features**

- Suede leather upper
- Rubber/phylon outsole
- Puncture resistant midsole
- Removable dual density PU comfort insole

**Benefits**

- Top quality premium hide, long lasting
- Light weight and flexible
- Underfoot protection
- PU collar for comfort

Upper	Suede & Canvas
Lining	Aerospacer
Insole	Removable Comfort Footbed
Outsole	Rubber/ Phylon Cemented
Sizes	UK 6-12 EU 40-46



**STANLEY**

**WORK IN PROGRESS**  
3a Holywell Hill, St Albans  
Hertfordshire, AL1 1ER, UK

**Tel: +44 (0) 1727 731 655**

**Fax: +44 (0) 1727 731 656**

**E-mail: [vinny.gallagher@w-i-p.co.uk](mailto:vinny.gallagher@w-i-p.co.uk)**

**We reserve the right to amend specifications  
without prior notice.**